8 F.D. FAN REMOVABLE TO PROVIDE ADDITIONAL SHIPPING CLEARANCE. OVERALL POWER EQUIPMENT COMPANY /2,, 847-541-8300 MOTOR 23 19 58'-0"

STEAM

- 1. 2 1/2"-300# SPARE (BLANKED)
- 2. 2 1/2"-300# SPARE (BLANKED)
- 2 1/2"-300# SAFETY VALVE CONNECTION (SAFETY VALVE MUST BE REMOVED FOR TRANSPORT)
- 4. 2"-300# SAFETY VALVE CONNECTION (SAFETŸ VALVE MUST BE REMOVED FOR TRANSPORT)
- 1" NPT DRUM VENT / AUX CONNECTION
- 6. 8"-300 # MAIN STEAM OUTLET CONNECTION
- 14. 1-1/2"-300# MUD DRUM BLOW OFF
- (2) 1-1/2"-300# LOW DRUM HEATING COIL CONNECTIONS ARE BLANKED.
- 17. 1" CONTINUOUS BLOWDOWN CONNECTION 20. 2"-300# SOOT BLOWER STEAM SUPPLY CONNECTION (BLANK ON FAR SIDE)

BOILER FEEDWATER

- 18. 2 1/2"-300# FEEDWATER SUPPLY CONNECTION
- 25. 2-1/2"-300# ECONOMIZER INLET CONNECTION
- 26. 2-1/2"-300# ECONOMIZER OUTLET CONNECTION

FUEL GAS

- 7. FLUE GAS STACK AND TRANSITION (REMOVED FOR TRANSPORT)
- 10. 3/4" NPT PILOT GAS CONNECTIONS (NATURAL OR PROPANE)
- 12. 3"-150 # FUEL GAS CONNECTION N.S.
- 13. 1 1/2"-150 # GAS VENT OUTLET N.S. (LOCATED N.S. NEAR SIDE OF TRAILER)

FUEL OIL

11. 3/4" NPT FUEL OIL INLET (LOCATED F.S. FAR SIDE OF TRAILER)

ATOMIZING STEAM

9. 1 1/2"-300# AUX ATOMIZING AIR / STEAM CONNECTION (LOCATED BEHIND CABINET)

ELECTRICAL

19. 480/60/3 POWER SUPPLY 179 AMPS

MISC.

- 8. F.D. FAN HOUSING
- 16. 1" NPT CHEMICAL FEED CONNECTION (LOCATED ON OPPOSITE SIDE OF TRAILER)
- 22. 3/4" NPT FURNANCE PRESS CONNECTION
- 23. WASHOUT
- 24. 1" NPT INSTRUMENT AIR CONNECTION

NOTE 1: A NATURAL GAS OR PROPANE PILOT IS REQUIRED FOR OIL

2: PROVIDE ADEQUATE WEATHER PROTECTION FOR BURNER, CONTROLS AND PERSONNEL

DESIGN DATA

OVERALL HEIGHT: OVERALL LENGTH: OVERALL WIDTH: NET WEIGHT (INCL TRAILER): CONTINUOUS CAPACITY: **DESIGN PRESSURE:** FEEDWATER TEMPERATURE: FURNACE VOLUME: CONVECTION HEATING SURFACE: 4,370 SQ. FT. RADIANT HEATING SURFACE: TOTAL HEATING SURFACE: GAS SUPPLY PRESSURE

OIL SUPPLY PRESSURE FEED WATER PRESSURE

INSTRUMENT AIR PRESSURE

59'-0" 10'-6" 94,600 LBS 75,000 PPH 395 PSIG 230 DEG F 1,105 CU. FT. 783.1 SQ. FT. 5,153.1 SQ. FT. (A.S.M.E.) 15 PSIG (REGULATED BY CUSTOMER) 30 PSIG FLOODED MAX. 75-100 PSIG ABOVE OPERATING PRESSURE 60 PSIG MIN.

14'-3"