STEAM

- 1. 2 1/2"-300# SPARE (BLANKED)
- 2. 2 1/2"-300# SPARE (BLANKED)
- 2 1/2"-300# SAFETY VALVE CONNECTION (SAFETY VALVE MUST BE REMOVED FOR TRANSPORT)
- 4. 2"-300# SAFETY VALVE CONNECTION (SAFETY VALVE MUST BE REMOVED FOR TRANSPORT)
- 1" NPT DRUM VENT / AUX CONNECTION
- 8"-300 # MAIN STEAM OUTLET CONNECTION
- 14. 1-1/2"-300# MUD DRUM BLOW OFF
- 15. 1-1/2"-300# LOW DRUM HEATING COIL CONNECTIONS ARE BLANKED.
- 17. 1" CONTINUOUS BLOWDOWN CONNECTION
- 20. 2"-300# SOOT BLOWER STEAM SUPPLY CONNECTION (BLANK ON FAR SIDE)
- 24. 1 1/2"-300# HEATING COIL (BLANKED)

BOILER FEEDWATER

18. 2-1/2"-300# FEEDWATER SUPPLY CONNECTION

FUEL GAS

- 7. FLUE GAS STACK AND TRANSITION (REMOVED FOR TRANSPORT)
- 10. 3/4" NPT PILOT GAS CONNECTIONS (NATURAL OR PROPANE)
- 12. 4"-150 # FUEL GAS CONNECTION
- 13. 2"-150 # GAS VENT OUTLET

FUEL OIL

11. 3/4" NPT FUEL OIL INLET (LOCATED ON END OF TRAILER)

ATOMIZING STEAM

1 1/2"-300# AUX ATOMIZING AIR / STEAM CONNECTION (LOCATED BEHIND CABINET)

ELECTRICAL

19. 480/60/3 POWER SUPPLY 179 AMPS

MISC.

59'-0"

POWER EQUIPMENT COMPANY

847-541-8300

- 8. F.D. FAN HOUSING
- 16. 1" NPT CHEMICAL FEED CONNECTION (LOCATED ON OPPOSITE SIDE OF TRAILER)
- 2"-300# CHEMICAL CLEANING CONNECTION
- 3/4" NPT FURNANCE PRESS CONNECTION WASHOUT
- 24. 1" NPT INSTRUMENT AIR CONNECTION
- NOTE 1: A NATURAL GAS OR PROPANE PILOT IS REQUIRED FOR OIL
- NOTE 2: PROVIDE ADEQUATE WEATHER PROTECTION FOR BURNER, CONTROLS AND PERSONNEL

DESIGN DATA

23

F.D. FAN REMOVABLE TO PROVIDE ADDITIONAL SHIPPING CLEARANCE.

OVERALL HEIGHT: OVERALL LENGTH: OVERALL WIDTH: NET WEIGHT (INCL TRAILER): CONTINUOUS CAPACITY: DESIGN PRESSURE: FEEDWATER TEMPERATURE: FURNACE VOLUME: CONVECTION HEATING SURFACE: RADIANT HEATING SURFACE: TOTAL HEATING SURFACE: GAS SUPPLY PRESSURE

OIL SUPPLY PRESSURE FEED WATER PRESSURE

INSTRUMENT AIR PRESSURE

14'-3" 59'-0" 10'-6" 94,600 LBS 75,000 PPH 395 PSIG

230 DEG F 1,128 CU. FT. 4,317 SQ. FT. 796 SQ. FT.

5,113 SQ. FT. (A.S.M.E.)

15 PSIG (REGULATED BY CUSTOMER) 30 PSIG FLOODED MAX. 75-100 PSIG ABOVE OPERATING PRESSURE

60 PSIG MIN.